

For Mac 10.4, 10.5, 10.6, 10.7

## How to install the Ethernet Evolis driver on MAC

1) Before starting the installation, plug the printer to the Mac and make sure you are logged with the **Administrator right**.

2) From <u>www.evolis.com</u>, download the Evolis Mac driver, run the setup installation and follow the instruction during the installation process (the Administrator rights are required).

3) Open the "System Preferences" to access the "Print and fax" section





000 P	rint & Fax	
Show All	Q	
000	Add Printer	0
<b>B A</b>	۹ 🐴	
Default Fax	IP Windows Search	
Protocol	: Line Printer Daemon - LPD	
Address		•
	Enter host name or IP address.	
Queue:		•
+ -	Leave blank for default queue.	
Name	: No Selection	
Defa	: No Selection	
Print Using	:	\$
		Add

4) Click on "+" to access the "Printer Browser" and select "IP printer "  $% \mathcal{A}^{(1)}$ 

5) Select "HP Jet Direct -Socket" option in the "Protocol" list and enter the printer IP address

000	Prir	nt & Fax		1. 30
Show All			Q	
	00	Add Printer	ſ	1
De	fault Fax	IP Windows	Search	
	Protocol:	HP Jetdirect - Socket		•
	Address:	192.168.30.26 Valid and complete address.		•
+ -	Queue:	Leave blank for default queue.		
i	Name: Location:	192.168.30.26		
Click the lock to prevent fu	Print Using: (	Generic PostScript Printer		•
				Add

6) Select the printer driver in the "Print Using" list and click on "OK" to finalize the driver installation

